

Custom Floral Coolers

SRC REFRIGERATION

6615 Nineteen Mile Road
Sterling Heights, MI 48314-2117
Toll Free: 800-521-0398
Fax: (586) 254-0485
www.SRC.us



STANDARD FEATURES AND SPECIFICATIONS

Model #: WDS Walk-in Display/Storage
 WD Reach-in Display

GENERAL

Walk-in cooler panels shall be of pre-fabricated modular construction designed for fast and easy field assembly, relocation, and future enlargement by the addition of like modular panels. Walk-in can be specified to standard or custom sizes with the required number of full view glass display doors to maximize merchandising and storage needs. Choice of attractive exterior factory finishes to eliminate finishing in the field.

PANEL CONSTRUCTION

Panels shall consist of interior and exterior metal skins precisely formed with steel dies and roll-forming equipment and thoroughly checked with gauges for accuracy. The metal skins shall be bonded tenaciously and permanently to the insulation. Hi-density panels have incredible flexural strength which eliminates the need for perimeter wood framing (old style construction) still used by some competition. To insure tight joints, all wall panels connect with positive cam-locking mechanisms.

INSULATION

Only solid core approved foamed in place or extruded insulation shall be used. Minimum thickness shall be four inches which exceeds insulation values (R-values) in Federal Energy Standard H.R.6 effective January 1st, 2009, for walk-in coolers and freezers. Only environmentally friendly expansion agents are to be used in the manufacture of insulated cores. No energy robbing structural wood rails shall be used except where necessary for glass door and/or window attachment.

METAL FINISH

Standard: White metal finish in/out
Optional: (12) attractive popular finishes available

INSULATED FLOOR

Floor panel construction shall be similar to that described in above Panel Construction section, but with a heavier gauge metal skin. Walking surfaces in open food approved boxes shall be stainless steel or aluminum. Galvanized metal will be used in closed food applications. Insulated floor panels are designed to withstand uniformly distributed stationary floor loads up to 600 lbs. psf. Contact factory for heavier load requirements and when optional metal finishes are required.

PANEL FASTENERS

Panel fasteners will be cam action male and female profile. Panels shall be fastened to adjacent panels by inserting a hex wrench in small-predrilled access ports on the male interior side. A clockwise turn of the wrench will activate a cam lever hook to catch a pin in the adjacent panel mechanism and draw the panels tightly together. Access ports are to be covered by press-fit plug buttons supplied with the panels.

DOOR PANEL ASSEMBLY

Door panel assembly includes UL Listed accessories either installed (whenever possible) or shipped loose. Construction and metal finish will match wall panels. Standard pre-hung entrance door includes the following features: *Two cam-lift self-closing hinges for smooth operation with built-in hold open feature *Cam-lift hinges allow for non-sweeping closure *Door latch *Inside safety release *Hydraulic door closure *Magnetic gasket *Thermometer. The bottom edge of walk-in door shall have an adjustable and replaceable wiper gasket. The door panel shall also include a UL Listed vapor-proof interior lamp and junction box for 120v/60/1 phase A/C service (15 amp maximum). For freezer application, pressure relief port(s) will be provided. A variety of door options are available for special circumstances. Contact factory for details.

GLASS DOORS / SHELVING

Merchandising display doors are available in a variety of sizes and finishes to meet design requirements. Each door standard with tempered insulated glass, magnetic air tight gasket, fluorescent light fixtures with lamp, low temperature ballast, and safety shield. Door and frame condensate heaters provide condensation protection under normal conditions. Optional heated glass available for high humidity conditions. Lights and heaters are prewired to interior junction box at top of frame, 120 volt, single phase service required.

REFRIGERATION

A complete selection of self contained to remote refrigeration systems available. Contact factory for proper selections and specification

CODE APPROVALS

Energy: Insulating R-Value exceeds Federal Std EISA (H.R.6)
Sanitation: UL-NSF Standard 7 Approved (ANSI / NSF7, 26PZ)
Safety: UL Listed Door Panel Assembly
Surface Burning Characteristics: Testing as per ASTM E84; flame spread rating of <25 and smoke development index <450

